



**19.230
LUMEN**

180W

15m

**LED
2835**



PACKING	INNER	MASTER
/	pcs	pcs
Colour box	2	2



TECHNICAL DATA

Name	ST915
Power supply	220V AC
Power supply provided	YES
Type of power supply provided	POWER CABLE
Lighting source	2835 SMD LED
Lighting power (W)	185
Electricity consumption (W)	185
Lumen	19230
IRC	>90.4
Light beam	DIFFUSE
LED lifespan (hours)	30000
Material	PLASTIC - OTHER
Power cord length (cm)	150
Cable section	H07RN-F 3x1.5
Cable length (meters)	15
Color	BLACK
Switch	NO
IP Protection	IP65
Insulation class	II
Energy class	F
Light colour	4000K
Dimmability	NOT DIMMABLE
Absorption (A)	8,3-9,1
Plug	Type E / F - 2 pin (EU Hybrid)
Operating temperature (°C)	-10°C + 40°C
Code eprel	1973871
Link db eprel	http://eprel.ec.europa.eu/qr/1973871
Warranty	2 YEARS
Width (mm)	230
Depth (mm)	190
Height (mm)	310
Net weight (Kg)	3.256

DESCRIPTION

Very bright: the strip can be installed anywhere in an instant. Once unrolled it turns on: 19.230 lumens of light (185W) illuminate the construction site. The warehouse, the garden.... It's a very powerful light. Wrapped on its convenient winder, it is 15 meters long and is very easy to transport and store. ATTENTION: it is necessary to completely unroll the strip during use! IP65 waterproof: it is protected from splashes of water. When it rains, the lamp works normally. Ideal for the construction site but also for all outdoor activities such as markets, stands, outdoor parties, emergency situations... Robust: it is not afraid of temperatures: from -10° to +40°C it works easily. 4000K natural light. The power cable is 1.5 meters long and is equipped with a European CEE 7/7 (Schuko) plug.

LOGISTIC INFORMATION

Packing type	Colour box
Pack length (mm)	210
Pack width (mm)	250
Pack height (mm)	335
Inner length (cm)	45
Inner height (cm)	37
Quantity in inner	2
Gross weight inner (kg)	7.800
ITF INNER	18003910114309
Quantity in master	2
How many pieces on 80x120 pallet (pz)	48
INTRASTAT Code	85395200
DEEE	0.42

