



PACKING	INNER	MASTER
/	pcs	pcs
Colour Box	4	4



TECHNICAL DATA

Power supply	220V AC
Power supply provided	YES
Type of power supply provided	POWER CABLE
Electricity consumption (W)	3000
Material	METAL
Power cord length (cm)	140
Color	BLACK
Switch	YES
Functions	1) FAN ONLY 2) NORMAL POWER 3) HIGH POWER
IP Protection	IP20
Insulation class	I
Absorption (A)	12,5 - 13,6
Plug	Type E / F - 2 pin (EU Hybrid)
Power adjustment (W)	25W/1500W/3000W
Timer	NO
Fuse required	YES
Auto reset thermostat	YES
Volume of hot air generated (m³h)	217
Heating area (m²)	60
Operating temperature (°C)	-15°C / +25°C
Warranty	2 YEARS
Width (mm)	265
Depth (mm)	210
Height (mm)	290
Net weight (Kg)	2.785

DESCRIPTION

3000W hot air generator; ceramic technology: unlike serpentine models, ceramic models are hot immediately; the "cannon" shape guarantees a better direction to the air flow. Excellent for temporary heating of a 60m³ room; useful for drying plasters. With fan function. Temperature regulation (25/1500 / 3000W), heats 217m³ / h; with safety thermostat (starts at 85 °). Equipped with 140cm cable with CEE 7/7 socket (schuko); hyper resistant metal structure; IPX0; use temperature: -15 ° c / + 25 ° c.

Packing type	Colour Box
Pack length (mm)	210
Pack width (mm)	285
Pack height (mm)	310
Packed product weight (kg)	14.300
Inner width (cm)	30
Quantity in inner	4
ITF INNER	18003910100401
Master length (cm)	45
Master width (cm)	30
Master height (cm)	66
Quantity in master	4
Master gross weight (kg)	14.300
How many pieces on 80x120 pallet (pz)	72
INTRASTAT Code	85162991
DEEE	0.42

