



PACKING	INNER	MASTER
/	pcs	pcs
<b>Colour box</b>	<b>4</b>	<b>4</b>



## TECHNICAL DATA

Name	MARSHALL
Power supply	220V AC
Power supply provided	YES
Type of power supply provided	POWER CABLE
Electricity consumption (W)	3000
Material	PLASTIC + METAL
Power cord length (cm)	140
Color	BLACK
Switch	YES
Functions	HOT + FAN
IP Protection	IP20
Insulation class	I
Absorption (A)	12,5-13,6
Plug	Type E / F - 2 pin (EU Hybrid)
Power adjustment (W)	7W/2000W/3000W
Timer	NO
Fuse required	YES
Auto reset thermostat	YES
Volume of hot air generated (m³h)	322
Heating area (m²)	30
Operating temperature (°C)	-15°C + 25°C
Warranty	2 YEARS
Width (mm)	290
Depth (mm)	130
Height (mm)	230
Net weight (Kg)	1.600

## DESCRIPTION

3000W hot air generator; ceramic technology: unlike serpentine models, ceramic models get hot immediately; the "cannon" shape guarantees better direction to the air flow. Excellent for temporary heating of a 30m2 room; useful for drying plaster. With fan function. Temperature regulation (7/2000/3000W), heats 322m3 /h; with safety thermostat (65° part). Equipped with 140cm cable with CEE 7/7 socket (schuko); hyper-resistant metal structure; IPX0; use temperature: -15°c / +25°c.



# STH3208

## DATA SHEET

Industrial hot air generator, ceramic 3KW

Packing type	Colour box
Pack length (mm)	180
Pack width (mm)	330
Pack height (mm)	290
Inner length (cm)	69
Inner height (cm)	38
Quantity in inner	4
Gross weight inner (kg)	9.000
ITF INNER	18003910114460
Quantity in master	4
How many pieces on 80x120 pallet (pz)	64
INTRASTAT Code	85162991
DEEE	0.21



### FUNZIONI FUNCTIONS



**IP20**



**SCHUKO  
220/240V  
3000W**

**1,4m**

