



PACKING	INNER	MASTER
/	pcs	pcs
<b>Brown Box</b>	<b>1</b>	<b>1</b>



## TECHNICAL DATA

Power supply	380-400V ~ 350Hz
Power supply provided	YES
Type of power supply provided	POWER CABLE
Electricity consumption (W)	5000
Material	METAL
Power cord length (cm)	140
Color	BLACK
Switch	YES
Functions	1) FAN ONLY 2) NORMAL POWER 3) HIGH POWER
IP Protection	IP20
Insulation class	I
Absorption (A)	7,2 - 7,6
Plug	Type E / F - 2 pin (EU Hybrid)
Power adjustment (W)	50W/3300W/5000W
Timer	NO
Fuse required	YES
Auto reset thermostat	YES
Volume of hot air generated (m³h)	423
Heating area (m²)	100
Operating temperature (°C)	-15°C / +25°C
Warranty	2 YEARS
Width (mm)	300
Depth (mm)	235
Height (mm)	345
Net weight (Kg)	4.200

## DESCRIPTION

5000W hot air generator; ceramic technology: unlike serpentine models, ceramic models are hot immediately; the "cannon" shape guarantees a better direction to the air flow. Excellent for temporary heating of a room of 100m3; useful for drying plasters. With fan function. Temperature regulation (50/3300 / 5000w), heats 423m3 / h; with safety thermostat (starts at 75 °). Equipped with 140cm h07rnf-4g 1.5mm2 cable with 380v three-phase industrial socket; hyper resistant metal structure; IPX0; use temperature: -15 ° c / + 25 ° c.



# STH5000W

DATA SHEET

5kW PTC heater

Packing type	Brown Box
Pack length (mm)	250
Pack width (mm)	330
Pack height (mm)	355
Packed product weight (kg)	4.800
Inner width (cm)	25
Quantity in inner	1
ITF INNER	18003910102535
Master length (cm)	33
Master width (cm)	25
Master height (cm)	36
Quantity in master	1
Master gross weight (kg)	4.800
How many pieces on 80x120 pallet (pz)	40
INTRASTAT Code	85162991
DEEE	0.71

